

- forecasting, A42.36
 general considerations, F19.1
 integration of systems, F19.23
 models, F19.1
 simulating, F19.3
 software selection, F19.5
 field survey audit, A38.17
 forecasting building needs, A42.36
 forward modeling, F19.1
 management, A36
 cost control, A36.10, 11
 emergency energy use reduction, A36.15
 energy audits, A36.7
 energy-efficiency measures (EEM),
 comparing, A36.11
 implementation, A36.15
 improving discretionary operations,
 A36.10
 resource evaluation, A36.1
 modeling, F19
 Bayesian analysis, F19.37
 calculating, F19.8
 change-point, F19.28
 regression, F19.30
 classical approach, F19.1
 data-driven approach, F19.2
 data-driven models, F19.27
 Gaussian process, F19.30
 heat balance method, F19.9
 hybrid inverse change point, F19.31
 in integrated building design, A58.9
 occupant behavior, F19.14
 primary system components, F19.21
 system controls, F19.23
 weighting-factor method, F19.10
 monitoring, A41
 applications, A41.1–5
 data, A41.6–15
 design and implementation methodology,
 A41.6
 documentation, A41.7, 15
 planning, A41.6, 15
 quality assurance, A41.6, 14
 recovery (See also **Heat recovery**)
 in air-handling units, S4.9
 air-to-air, S26; S41.4
 in chemical industry, R46.4
 industrial environments, A31.6
 renewable, F35.2
 resources, F34; F35.2
 demand-side management (DSM), F34.4
 integrated resource planning (IRP), F34.3
 nonrenewable, F34.2
 renewable, F34.2
 United States, F34.7
 world, F34.4
 savings verification, A41.2
 self-imposed budgets, F35.8
 storage, S51
 wheels, S26.9
Energy efficiency ratio (EER)
 evaporative cooling, A52.8
 geothermal systems, A34.15
 room air conditioners, S50.1, 3
 unitary equipment, S49.6
Energy savings performance contracting (ESPC), A37.8
Energy transfer station, S12.37
- Engines, S7**
 air systems, compressed, S7.13
 applications, S7.45
 continuous-duty standby, S7.4
 controls and instruments, S7.15
 exhaust systems, S7.14
 expansion engines, S7.31
 fuels, F28.9; S7.11
 cetane number, F28.9
 heat recovery, S7.33
 heat release, A17.1
 jacket water system, S7.13
 lubrication, S7.13
 noise control, S7.16
 performance, S7.10
 reciprocating, S7.9, 10
 vibration control, S7.16
 water-cooled, S7.14
Engine test facilities, A17
 air conditioning, A17.1
 dynamometers, A17.1
 exhaust, A17.2
 noise levels, A17.4
 ventilation, A17.1, 4
Enhanced tubes. See Finned-tube heat transfer coils
Enthalpy
 calculation, F2.4
 definition, F2.2
 foods, R19.8
 water vapor, F6.10
 wheels, S26.9
Entropy, F2.1
 calculation, F2.4
Environmental control
 animals. See **Animal environments**
 humans. See **Comfort**
 plants. See **Plant environments**
 retail food stores, store ambient effect, R15.3
Environmental control system (ECS), A12
Environmental health, F10
 biostatistics, F10.3
 epidemiology, F10.3
 exposure, F10.6
 industrial hygiene, F10.3
 microbiology/mycology, F10.3
 physical hazards
 electrical hazards, F10.19
 electromagnetic radiation, F10.21
 noise, F10.20
 thermal comfort, F10.16
 vibrations, F10.19
 standards, F10.12
Environmental tobacco smoke (ETS)
 contaminants, A46.3
 secondhand smoke, F11.19
 sidestream smoke, F10.6
 superheated vapors, F11.2
EPDI. See Economic performance degradation index (EPDI)
Equipment vibration, A48.43; F8.17
ERF. See Effective radiant flux (ERF)
ESPC. See Energy savings performance contracting (ESPC)
 Ethylene glycol, in hydronic systems, S13.24
ETS. See Environmental tobacco smoke (ETS); Electric thermal storage (ETS)
Evaluation. See Testing
- Evaporation, in tubes**
 forced convection, F5.4, 7
 natural convection, F5.1
Evaporative coolers. (See also Refrigerators)
 liquid (See also **Evaporators**)
 in chillers, A1.5; S39.18; S43.5, 7, 13
Evaporative cooling, A52
 applications
 air cleaning, A52.2; S41.9
 animal environments, A24.4; A52.14
 commercial, A52.10
 dehumidification, A52.2; S41.8
 gas turbines, A52.13
 greenhouses, A24.13; A52.14
 humidification, A52.2; S41.8
 industrial
 air conditioning, A14.8
 area cooling, A52.12
 process cooling, A52.13
 spot cooling, A52.12
 laundries, A52.13
 makeup air pretreatment, S41.6
 motors, A52.12
 power generation facilities, A52.14
 precooling, S41.6
 produce storage, A52.14
 residential, A52.10
 wood and paper products facilities, A52.13
 cooling towers, S40.1
 direct, A52.1, 2; S41.1
 economics, A52.17
 entering air condition, A52.18
 equipment
 indirect, S41.3
 maintenance, S41.9
 two-stage, S41.5
 exhaust requirement, A52.10
 heat recovery and, A52.7; S41.5
 humidification, S22.10
 indirect, A52.1, 2; S41.3
 psychometrics, A52.1, 11, 17, 18
 stagel
 booster refrigeration, A52.8, 18
 two-stage (indirect/direct), A52.11, 17;
 S41.5
 water treatment, A49.18; S41.10
Legionella pneumophila, S41.10
Evaporators. (See also Coolers, liquid)
 air conditioners, room, S50.2
 ammonia refrigeration system equipment, R2.8
 automobile air conditioning, A10.6, 11
 chemical industry refrigeration, R46.7
 halocarbon refrigeration systems, piping,
 R1.23
 liquid overfeed systems, R4.6
Exfiltration, F16.2
Exhaust
 animal buildings, A24.6
 clean spaces, A18.19, 23
 engines
 heat recovery, S7.35
 installation recommendations, S7.14
 engine test facilities, A17.2
 industrial environments, A14.8; A32.1
 kitchens, A33.36
 laboratories, A16.3, 9
 stack height, A16.13
 photographic processing areas, A22.3

ground source

- industrial, R29.1
- soil, R45.3, 4
- Friction, in fluid flow**
 - conduit, F3.6
 - wall, F3.3
- Fruit juice, R38**
- Fruits**
 - dried
 - storage, R42.7
 - thermal properties, R19.1
 - fresh
 - air transport, R27.1
 - apples, storage, A52.14; R35.1
 - apricots, R35.13
 - avocados, R36.8
 - bananas, R36.5
 - berries, R35.13
 - cherries, sweet, R35.12
 - citrus, A52.14; R36.1
 - cooling, R28.1
 - deciduous tree, R35
 - desiccation, R21.1
 - deterioration rate, R21.1
 - display refrigerators, R15.8
 - figs, R35.13
 - grapes, R35.8
 - mangoes, R36.8
 - nectarines, R35.12
 - peaches, R35.12
 - pears, R35.6
 - pineapples, R36.8
 - plums, R35.11
 - storage diseases, R35.1
 - strawberries, R35.13
 - thermal properties, R19.1
 - vine fruits, R35.1
 - frozen, R40.5
- Fuel cells, combined heat and power (CHP), S7.22**
- Fuels, F28**
 - classification, F28.5
 - combustion, F28
 - altitude effects, F28.3; S7.8, 10, 19; S31.10
 - engines, S7.11
 - flammability limits, F28.1
 - gaseous, F28.5
 - heating value, F28.3; S7.12
 - ignition temperature, F28.2
 - liquid, F28.7
 - oil. *See* **Oil, fuel**
 - systems, S7.12
 - solid, F28.9
 - turbines, S7.20
- Fume hoods, laboratory exhaust, A16.3**
- Fungi**
 - and moisture, A62.10
 - pathogens, F10.8
 - spores, F11.2
- Furnaces, S33**
 - air cleaners and filters, S33.2
 - airflow configurations, S33.2
 - air supply, S35.28
 - burners, S31.1; S33.2
 - casings, S33.1
 - codes, S33.9
 - commercial, S33.5
 - efficiency, S33.9
 - components, S33.1
 - controls, S33.2, 5
 - derating, S31.10
 - duct, S33.5
 - duct furnaces, S31.6
 - electric, S33.4, 9
 - fans and motors, S33.2
 - floor furnaces, S34.2
 - gas-fired, S33.1, 8
 - codes, S33.9
 - commercial, S33.5
 - installation, S33.9
 - residential, S33.1
 - standards, S33.10
 - upflow, S33.5
 - humidifiers, S33.2
 - installation, S33.9
 - location, S33.6
 - natural gas, S31.11; S33.1, 4, 8
 - residential, S33.1, 8
 - venting, S33.2; S35.20
 - oil, S33.4, 9
 - venting, S35.21
 - performance criteria, S33.8
 - propane, S33.4, 9
 - regulating agencies, S33.10
 - residential, A1.3; S33.1
 - floor furnaces, S34.2
 - indoor or outdoor, S33.4
 - performance criteria, S33.8
 - selection, S33.6
 - selection, S33.6
 - standards, S33.10
 - stokers, S31.17
 - thermal storage, S51.18
 - unducted, S33.5
 - upflow, S33.5
 - venting, S35.20, 21
 - wall furnaces, S34.1
- Galleries. *See* Museums, galleries, archives, and libraries**
- Garages**
 - automotive repair, A15.21
 - bus, A15.22
 - contaminant criteria, A15.19
 - parking, A3.8; A15.18
 - ventilation
 - airflow rate, A15.19
 - control, A15.20
 - equipment, A15.33
 - residential, F16.21
 - system configuration, A15.21
- Gases**
 - compressed, storage, A16.8
 - drying, S24.13
 - liquefaction, R47.6
 - purification, R47.16, 19
 - separation
 - gaseous oxygen, R47.18
 - Gibbs phase rule, R47.16
- Gas-fired equipment, S34. (*See also* Natural gas)**
 - noise, F28.19
- Gas vents, S35.1**
- Gaussian process (GP) models, F19.30**
- GCHP. *See* Ground-coupled heat pumps (GCHP)**
- Generators**
 - absorption units, R18.1, 10
 - combined heat and power (CHP), S7.40
- Geothermal energy, A34**
 - corrosion control, A34.6
 - direct-use systems, A34.3
 - cooling, A34.9
 - equipment, A34.5
 - heating, A34.8
 - service water heating, A34.8
 - district heating, A34.8
 - geothermal fluids, A34.1
 - disposal, A34.4
 - temperature, A34.1, 4
 - ~~ground-source heat pump (GSHP) systems, A34.10, 38, 39, 41~~
 - heat exchangers, A34.7, 37
 - materials performance, A34.5
 - resources, A34.1
 - valves, A34.7
 - water wells
 - flow rate, A34.3
 - pumps, A34.6, 36
 - terminology, A34.33
 - water quality testing, A34.4
- Geothermal heat pumps (GHP), A34.10**
- Glaser method, F25.15 *See* Ground Source Heat Pumps, Chapter AX**
- Glazing**
 - angular averaging, F15.17
 - glass, F15.1
 - plastic, F15.32
 - solar-optical properties, F15.14
 - spectral averaging, F15.17
 - spectral range, F15.17
 - systems, F15.16
- Global climate change, and refrigerants, F29.1**
- Global warming potential (GWP), F29.5**
- Glossary, of refrigeration terms, R50**
- Glycols, desiccant solution, S24.2**
- Graphical symbols, F38**
- Green design, and sustainability, F35.1**
- Greenhouses. (*See also* Plant environments)**
 - evaporative cooling, A52.14
 - plant environments, A24.10
- Grids, for computational fluid dynamics, F13.4**
- Ground-coupled heat pumps (GCHP)**
 - closed-loop ground-source, A34.10
 - heat exchanger, S49.13
- Ground-coupled systems, F19.23**
- Ground-source heat pumps (GSHP), A34.1, 10**
- Groundwater heat pumps (GWHP), A34.32**
- GSHP. *See* Ground-source heat pumps (GSHP)**
- Guard stations, in justice facilities, A9.5**
- GWHP. *See* Groundwater heat pumps (GWHP)**
- GWP. *See* Global warming potential (GWP)**
- Gymnasiums, A5.5; A7.3**
- HACCP. *See* Hazard analysis critical control point (HACCP)**
- Halocarbon**
 - coolants, secondary, F31.12
 - refrigerant systems, R1.1
- Hartford loop, S11.3**
- Hay, drying, A25.8**
- Hazard analysis and control, F10.4**
- Hazard analysis critical control point (HACCP), R22.4**

- in meat processing facilities, R30.1
 - Hazen-Williams equation**, F22.6
 - HB**. *See* Heat balance (HB)
 - Health**
 - airborne pathogens, F10.8
 - asbestosis, F10.5
 - carbon monoxide, F10.15
 - coalworker's pneumoconiosis, F10.5
 - in justice facilities, A9.4
 - Legionella pneumophila*, F10.7
 - and moisture problems, F25.16
 - silicosis, F10.5
 - synthetic vitreous fibers (SVFs), F10.6
 - Health care facilities**, A8. (*See also specific types*)
 - air quality, A8.3
 - design criteria, A8.5
 - disease prevention, A8.2
 - regulatory requirements, A8.1
 - sustainability, A8.13
 - Health effects, mold**, A62.1
 - Heat**
 - flow rates, F18.1
 - latent
 - respiratory loss, F9.4
 - skin loss, F9.3, 10
 - sensible
 - respiratory, F9.4
 - skin, F9.3
 - space extraction rate, F18.2
 - timers, S11.13
 - transfer, F4; F25; F26; F27
 - Heat and moisture control**, F27.1
 - Heat balance (HB)**, S9.23
 - air, F18.19
 - conduction transfer function, F18.20
 - cooling load calculation methods, F18.2, 16
 - equations, F18.20
 - input procedure, F18.21
 - model, F18.17
 - studies, S9.23
 - surface, F18.17
 - Heat balance method**, F19.3
 - Heat capacity**, F25.1
 - Heat control**, F27
 - Heaters**, S34
 - automobiles, A10.5
 - catalytic, S34.1
 - control, S34.2, 4
 - direct-contact, S15.5
 - electric, S16.2; S34.3
 - fireplaces, S34.5
 - gas, S16.1; S31.6; S31.7; S34.1
 - control valves, S34.2
 - efficiency requirements, S34.2
 - infrared, S16.1
 - room, S34.1
 - thermostats, S34.2
 - wall furnaces, S34.1
 - hot-water, S28.4
 - hydronic snow melting, A51.12
 - infrared, S16.1; S31.7
 - indirect, S31.7
 - oil-fired, S16.3
 - radiant, A54.1, 4, 8
 - in-space, S34.1
 - kerosene, S34.3
 - oil, S16.3; S34.3
 - radiant, S31; S34
 - electric, S16.2
 - gas-fired, S16.1; S31.7; S34.1
 - infrared, S31.7
 - oil-fired infrared, S16.3
 - panels, S34.4
 - quartz, S34.4
 - residential, S34.1
 - room, S34.1
 - solid fuel, S34.4
 - standards, S34.6, 7
 - steam, S28.4
 - stoves, S34.5
 - testing, S34.7
 - unit, S28.4; S31.6
 - control, S28.6
 - location, S28.4
 - maintenance, S28.8
 - pipng, S28.7
 - ratings, S28.6
 - selection, S28.4
 - sound level, S28.6
 - types, S28.4
 - ventilators, S28.1
 - water, A50
- Heat exchangers**, S48
 - air-to-air energy recovery, S26.1
 - heat pipes, S26.14
 - liquid-desiccant cooling systems, S26.18
 - rotary enthalpy wheels, S26.9
 - thermosiphon, S26.16
 - twin-tower enthalpy recovery loops, S26.19
 - animal environments, A24.4
 - antifreeze effect on, S13.24
 - chimneys, S35.31
 - counterflow, F4.22; S48.1
 - district heating and cooling, S12.42
 - double-wall construction, S48.3
 - effectiveness, capacity rate ratio, F4.22
 - enhanced surfaces, F5.19
 - fouling, S48.6
 - furnaces, S33.1
 - geothermal energy systems, A34.7, ~~48~~
 - halocarbon refrigeration systems, R1.29
 - heat transfer, S48.1
 - installation, S48.6
 - liquid suction, R1.29
 - number of transfer units (NTU), F4.22
 - parallel flow, F4.22
 - plate, F4.24; R1.30; S42.2
 - brazed, S12.42; S48.3
 - components, S48.4
 - gasketed, S12.42; S48.3
 - plate-and-frame, S12.42
 - pressure drop in, F5.18
 - welded, S12.43; S48.3
 - selection, S48.5
 - shell-and-coil, R1.30; S12.43; S48.2
 - shell-and-tube, R1.30; S12.43; S42.1
 - components, S48.4
 - converters, S48.2
 - straight-tube, S48.2
 - tube-in-tube, R1.30; S42.1
 - U-tube, S48.2
 - solar energy, S37.15
 - systems
 - solar energy, A35.11
- steam, S11.3
 - water, medium- and high-temperature, S15.6
- wraparound, S25.10
- Heat flow**, F25. (*See also Heat transfer*)
 - and airflow, F25.14
 - through flat building component, F25.7
 - hygrothermal modeling, F25.15
 - and moisture, F25.14
 - paths, series and parallel, F25.7
- Heat flux**, F25.1
 - radiant panels, S6.2
- Heat gain**. (*See also Load calculations*)
 - appliances, F18.7
 - calculation
 - solar heat gain coefficient (SHGC), F18.18
 - standard air values, F18.15
 - control, F25; F26; F27
 - electric motors, F18.6
 - engine test facilities, dynamometers, A17.1
 - fenestration, F18.16
 - floors, F18.25
 - hospital and laboratory equipment, F18.11
 - humans, F18.3
 - laboratories, A16.2
 - latent, permeable building materials, F18.15
 - lighting, F18.3
 - office equipment, F18.11
 - radiant panels, S6.6
 - space, F18.1
- Heating**
 - absorption equipment, R18.1
 - animal environments, A24.4
 - control, A42.39
 - equipment, S3.1, S27-S34; S49
 - baseboard units, S36.2
 - boilers, S32.1
 - convectors, S36.1
 - finned-tube units, S36.2
 - furnaces, S33.1
 - radiators, S36.1
 - geothermal energy systems, A34.8
 - greenhouses, A24.11
 - industrial environments, A14.7
 - infrared, S16.1
 - radiant, A54.1, 8
 - nonresidential, S13.17
 - passive, F19.27
 - places of assembly, A5.1
 - plant growth chambers, A24.17
 - power plants, A27.11
 - residential, A1.1
 - solar energy, S37.1
 - systems
 - all-air, S4.2, 5
 - selection, S1.1, 9
 - small forced-air, S10.1
 - solar energy, A35.15, 26
 - steam, S11.1
 - thermal storage, S51.16
- Heating load**
 - calculations, F18.30
 - central plant, S3.2
 - residential calculations, crawlspace heat loss, F17.11
- Heating seasonal performance factor (HSPF)**, S49.6
- Heating values of fuels**, F28.3, 9, 10
- Heat loss**. (*See also Load calculations*)

Pressure drop. (See also Darcy-Weisbach equation)

- correlations, F5.15
- district heating and cooling, S12.13
- pipe design, F22.1
- in plate heat exchangers, F5.18
- two-phase fluid flow, F5.15

Primary-air systems, S5.10**Printing plants, A20**

- air conditioning, A20.1
- air filtration, A20.4
- binding areas, A20.5
- colloidal printing rooms, A20.4
- letterpress areas, A20.2
- lithographic pressrooms, A20.3
- paper moisture content control, A20.2
- platemaking rooms, A20.2
- relief printing areas, A20.2
- rotogravure pressrooms, A20.4
- salvage systems, A20.4
- shipping areas, A20.5
- ink drying, A30.3

Prisons, A9.4**Produce**

- desiccation, R21.1
- deterioration rate, R21.1
- display refrigerators, R15.8

Product load, R15.5**Propane**

- commercial, F28.5
- furnaces, residential, S33.9

Propylene glycol, hydronic systems, S13.24**Psychrometers, F1.13****Psychrometrics, F1**

- air handlers, S4.4
- altitude effects, F1.1, 14
- chart, F1.14
 - adiabatic mixing, F1.17
 - heat absorption and moisture gain, F1.18
 - moist air, cooling and heating, F1.16
 - thermodynamic properties, F1.14
- evaporative cooling systems, A52.1, 10, 17, 18
- humidity parameters, F1.12
- industrial drying, A30.1
- moist air
 - standard atmosphere, U.S., F1.1
 - thermal conductivity, F1.20
 - thermodynamic properties, F1.2, 14
 - transport properties, F1.19
 - viscosity, F1.19
- perfect gas equations, F1.12
- water at saturation, thermodynamic properties, F1.6

PTACs. See Packaged terminal air conditioners (PTACs)**PTHPs.** See Packaged terminal heat pumps (PTHPs)**Public buildings.** See Commercial and public buildings; Places of assembly**Pumps, F19.18**

- cavitation, S14.2
- centrifugal, S44
 - affinity laws, S44.8
 - antifreeze effect on, S13.24
 - arrangement, S13.7; S44.12
 - pumping, S44.12
 - standby pump, S44.13
 - casing, S44.2

- cavitation, S44.10
- commissioning, S44.15
- construction, S44.1
- efficiency, best efficiency point (BEP), S44.7

- energy conservation, S44.15
- impellers, trimming, S44.7, 9, 10
- installation, S44.15
- mixing, S13.8
- motors, S44.15
- operation, S44.15
- performance, S13.6, S44.4
- power, S44.7
- radial thrust, S44.10
- selection, S44.11
- types, S44.2
- variable-speed, S13.9

- chilled-water, A42.12, 13, 24
 - sequencing, A42.12, 15
- condenser water, A42.24
- as fluid flow indicators, A38.13
- geothermal wells, ~~A34.36~~
 - lineshaft, A34.6
 - submersible, A34.6

- horsepower, S44.7
- hydronic snow melting, A51.13
- liquid overflow systems, R4.4
- net positive suction head, S14.1, 2
- solar energy systems, A35.11
- systems, water, S13.6; S15.5
- variable-speed, A42.13, 26

Purge units, centrifugal chillers, S43.11**PV systems.** See Photovoltaic (PV) systems; Solar energy**Radiant heating and cooling, A55; S6.1; S15; S33.4.** (See also Panel heating and cooling)

- applications, A54.8
- asymmetry, A54.5
- beam heating design, A54.4; S16.5
- control, A47.4
- design, A54.2, 3
- direct infrared, A54.1, 4, 8
- equations, A54.2
- floor radiation, A54.5
- infrared, A54.1, 4, 8; S16
 - beam heater design, S16.5
 - control, S16.4
 - efficiency, S16.4
 - electric, S16.2
 - energy conservation, S16.1
 - gas-fired, S16.1
 - indirect, S16.2
 - maintenance, S16.5
 - oil-fired, S16.3
 - precautions, S16.4
 - reflectors, S16.4
- installation, A54.8
- intensity, S16.1
- panels, A54.1, 8; S34.4; S36.6
 - applications, A54.8
 - control, A47.4
 - heating, S34.4
 - hydronic systems, S36.6
 - radiation patterns, A54.5
- snow-melting systems, A51.16
- terminology
 - adjusted dry-bulb temperature, A54.1
 - ambient temperature, A54.1

- angle factor, S16.5
- effective radiant flux (ERF), A54.2; S16.5
- fixture efficiency, S16.4
- mean radiant temperature (MRT), A54.1; S6.1
- operative temperature, A54.1
- pattern efficiency, S16.4
- radiant flux distribution, S16.6
- radiation-generating ratio, S16.4
- test instruments, A54.7
- total space heating, A54.6

Radiant time series (RTS) method, F18.2, 22

- factors, F18.22
- load calculations, nonresidential, F18.1

Radiation

- atmospheric, A35.5
- diffuse, F15.17, 20
- electromagnetic, F10.21
- ground-reflected, F15.17
- optical waves, F10.22
- radiant balance, F4.15
- radio waves, F10.22
- solar, A35.3
- thermal, F4.2, 11; S6.1
 - angle factors, F4.13
 - blackbody, F4.12
 - black surface, F4.2
 - display cases, R15.5
 - energy transfer, F4.11
 - exchange between surfaces, F4.14
 - in gases, F4.16
 - gray, F4.2, 12
 - heat transfer, F4.2
 - infrared, F15.17
 - Kirchhoff's law, F4.12
 - monochromatic emissive power, F4.12
 - nonblack, F4.12
 - spectral emissive power, F4.12
 - transient, F4.8

Radiators, S36.1, 5

- design, S36.3
- nonstandard condition corrections, S36.3
- types, S36.1

Radioactive gases, contaminants, F11.21**Radiometers, A54.7****Radiosity method, F19.26**

- Radon, F10.16, 22
 - control, F16.21
 - indoor concentrations, F11.19
 - removal, A46.15

Rail cars, R25. (See also Cargo containers)

- air conditioning, A11.5
- air distribution, A11.7
- heaters, A11.7
- vehicle types, A11.5

Railroad tunnels, ventilation

- design, A15.17
- diesel locomotive facilities, A15.27
- equipment, A15.33
- locomotive cooling requirements, A15.17
- tunnel aerodynamics, A15.18
- tunnel purge, A15.18

Rain, and building envelopes, F25.4**RANS.** See Reynolds-Averaged Navier-Stokes (RANS) equation**Rapid-transit systems.** See Mass-transit systems**Rayleigh number, F4.20**